



Dry epoxy resin filling capacitor with aluminum can type G78

1、 Outline:

2、 Characteristics:

- Double-sided metallized polypropylene film
- Low inductance
- Low loss
- Low ESR
- Withstand high current
- Withstand high surge current
- Withstand peak current
- Self-healing
- Long service life
- Easy to install



3、 Applications:

UPS, frequency converter, electroplating power supply, ultrasonic equipment, inverter welding machine, high power switching circuit, IGBT module, and etc.

4、 Performance indicators:

Rated voltage	500Vdc~6000Vdc
Rated capacitance	0.1 μ F~10 μ F
Capacitance tolerance	\pm 5% , \pm 10%
Dielectric Loss Tangent	2×10^{-4}
Loss Tangent	$\bullet 25 \times 10^{-4}$ (1V, 100Hz)
Withstand voltage between terminals	1.5Un, 10/60s
Withstand voltage between terminal and case	(2Un+1000) Vac, 60s
Operating temp. (case)	-40 $^{\circ}$ C~+70 $^{\circ}$ C
Hot-spot temperature	-40 $^{\circ}$ C~+85 $^{\circ}$ C
Expected life (hour)	>100000
Climate category	40/85/56
Encapsulation	Aluminum
Impregnant	Epoxy resin, PU resin